

item number / EOL.CE.DLUG.B9

AlaatreUG, 9W Recessed UGR19 LED Downlight

Application

residential or commercial indoor space

Design Specifications

Recessed LED Downlight

9 watt, SMD technology, 900lumens

input:220-240v , frequency:50/60Hz

50,000 hours

PF 0.9, 3 CCT changeable colour temperature

CRI:80a , beam angle 60 deg

Dimmable with Universal and trailing edge dimmer

90mm cutout, Flex and plug




Performance

Dimmable – dimmable Trailing edge

Technical Specification

Model No.	Description	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle
EOL.CE.DLUG.B9	9w UGR-19. dimmable downlight	220-240VAC	9w	900lm	Tri-colour	60
EOL.CE.DLUG.W9	9w UGR-19. dimmable downlight	220-240VAC	9w	900lm	Tri-colour	60
CRI	COLOUR BODY		box Dimension			
80+	White & BLACK		98mm* 103mm			

Dimensions



CERIAN

Cutout 90mm

D103mm

H86mm

SPECIFICATIONS

Model No.:	EOL.CE.DLUG.B9	□
	EOL.CE.DLUG.W9	□
Input Volt:	220-240Vac 50/60Hz	
Power:	9W	
Lumens:	900lm	
CCT :	3000K 4000K 5000K	
Dimmable with	Universal and trailing edge dimmer	